



MATERIAL SPECIFICATION & INSTALLATION GUIDE

PRODUCT ITEM CODE & DESCRIPTION

ML 327 ~ 336 - DISABLED STRAIGHT SSS GRAB RAILS



COMPONENT MATERIALS:

#304 Grade Stainless Steel 32mm \varnothing Tubing, & Twist Lock Flange Covers - #3 Finish / Concealed Multi-point Fix 75mm \varnothing Mounting Flanges / All Welds Seamless and Linished / *Can also be provided in Polished or Powder Cote Finish*

DIMENSIONS:

Lengths Available from 300 to 2400mm: As Detailed In Metlam Architectural Binder and/or WEB Site

INSTALLATION:

These units are to be surface mounted and are subject to compliance to Australian Building Code Regulations and/or AS 1428.1 for height location and fitment for disabled/accessible use as may be applicable, which is the responsibility of the installation contractor.

NOTE: Shower Applications - it is recommended that a "wet area" rated silicone be placed between the mounting plate and surface being affixed to, and onto screw head/neck section at installation in minimising ingress of water or cleaning agents, as they can cause tea-staining or forms of galvanic reaction and result in an unsightly appearance.

"Wet area" rated fasteners/anchors are not included with the units and are the responsibility of the installation contractor, as is the compliance re fitment of internal wall blocking, such as noggins for anchoring the unit to, using appropriate hardware.



All Metlam Disabled/Accessible Products Comply To AS 1428.1 When Correctly Installed

These units should only be installed by a competent tradesperson and Metlam Australia takes no responsibility for any damage to walls or fixtures due to incorrect installation.