

# MATERIAL SPECIFICATION & INSTALLATION GUIDE

## PRODUCT ITEM CODE & DESCRIPTION

### **ML 263 ~ RECESSED STAINLESS STEEL DUAL TOILET ROLL HOLDER W/HOOD**



## COMPONENT MATERIALS / FEATURES:

#304 Grade Stainless Steel body/hoods - #3 Finish / Chrome Plated ABS Rollers  
(Compression Release for Paper Replacement) / Holds Two Standard Toilet Paper Rolls

## DIMENSIONS:

Overall ~ 318mm W x 159mm H x 45mm D

Wall Opening ~ 299mm W x 140mm H x 51mm D

## INSTALLATION:

1. May be subject to Australian Building Code Regulations for height/location fixing and/or subject to placement as per architectural drawings, which in all cases is the responsibility of the installer re compliance.
2. Create wall opening to dimensions noted. Dependent upon cavity depth to surface material, a noggin can be installed so as it is 50mm in depth from the surface being fitted to for rigid & secure fixing (*refer points 3. & 5. for explanation*) with appropriate fasteners
3. On rear of recessed toilet roll sections, place a suitable amount of an adhesive material such as Liquid Nails® or a similar commercial grade high strength bonding agent
4. On the rear of the surround surface area, place a solid bead of a suitable commercial grade "wet area" silicone sealant around the full perimeter
5. Place dispenser into cavity, level and push firmly so as unit sits flush with outer wall section and creates a solid interface with the internal substrate or noggin, secure fasteners
6. Clean off any excess silicone and leave to cure/set for at least 24 hours before use

*These units should only be installed by a competent tradesperson and Metlam Australia takes no responsibility for any damage to walls or fixtures due to incorrect installation.*